



Application Industry: Waterborne Polyurethane Waterborne Epoxy
Industrial Coatings Printing Inks

Product Name: Antifoam RK-66T

RK-66T has excellent defoaming and anti-foaming properties as well as excellent compatibility, and can effectively prevent microfoam generation in high and low viscosity systems. RK-66T is suitable for water-based systems such as container paints, wood furniture paints, architectural coatings, industrial coatings and water-based printing inks.

Product property:

Outstanding defoaming and anti-foaming properties
Excellent dispersibility
High system compatibility
Easy to add
Suitable for all kinds of high and low viscosity and high solids systems.

Main physical and chemical properties:

Item	Range
Appearance	Colorless or light yellow slightly turbid liquid
Active content	100%
pH	6.0-8.0
Ionicity	Non-ionic type

Application Process:

It can be directly added and used, the addition amount is 0.1%-2%, and the best addition amount is determined according to the actual situation on site.

Key Applications

Various latex systems
Paints and varnishes in water-based systems
Waterborne polyurethane, acrylic acid, epoxy systems

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses



Information of manufacturers and products

Product name	Antifoam
Model	RK-66T
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: 1267 Qianpu South Road, Siming District, Xiamen City, Fujian Province, China
Tel/Fax	15359255189

Product content

Pure or mixture	Mixture
English name	Polyether modified siloxane

Dangerous marks

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage	——	
Special damage	——	

Packaging & Storage

Package	25kg/ 50kg/120kg/ 200kg plastic pail or 1000kg IBC
Storage Condition	Room Temperature Storage (5°C-40°C) . Avoid direct sun light, shelf life is 12 months.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application