



Application Industry: Waterborne Colour Paste Grinding Emulsion Polymerisation
Automotive Production Line Coatings Adhesives

Product Name: Antifoam RK-26T

RK-26T is a special modified polyether defoamer with excellent defoaming, foam inhibition and system compatibility. It is widely used in water-based systems for emulsion polymerisation, colour paste grinding, adhesives, plastic paints, industrial paints, wood furniture coatings, automotive production line coatings, architectural coatings, paper coatings, printing inks, etc.

Product property:

Outstanding defoaming and anti-foaming properties
Suitable for grinding processes
High system compatibility
Shear resistance

Main physical and chemical properties:

Item	Range
Appearance	Colorless slightly turbid liquid
Active content	100%
pH	6.0-8.0
Ionicity	Non-ionic type

Application Process:

Before use, it should be fully stirred. When used in the ink (paint) process, it must be high sheared or pre-diluted. The recommended addition amount is 0.1%-1%, and the best addition amount depends on the test of different emulsion systems.

Key Applications

Waterborne Colour Paste Grinding
Automotive Line Coatings
Architectural Coatings
Pure acrylic emulsion
Water-based inks, adhesives and other systems

LIMITATIONS



This product is neither tested nor represented as suitable for medical or pharmaceutical uses

Information of manufacturers and products

Product name	Antifoam
Model	RK-26T
Manufacturer	Xiamen Rickman Chemical Technology CO., Ltd. Add: 1267 Qianpu South Road, Siming District, Xiamen City, Fujian Province, China
Tel/Fax	15359255189

Product content

Pure or mixture	Mixture
English name	Special modified polyether

Dangerous marks

Human-body health effect	Skin contact	Slightly skin allergic for variety of people
	Eye contact	Eye allergic
	Swallow	No data
Environment effect	No data	
Physical/chemical damage	—	
Special damage	—	

Packaging & Storage

Package	25kg/ 50kg/120kg/ 200kg plastic pail or 1000kg IBC
Storage Condition	Room Temperature Storage (5°C-40°C) . Avoid direct sun light, shelf life is 12 months.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of Rickman products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end application